TECHNICAL SPECIFICATION

HEAD PROTECTION



EVO®3 Mid Peak OneTouch™ Slip Ratchet Non Vented

White / AJE160-000-100



DESCRIPTION

The EVO®3 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment[™] harness system. EVO®3 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®3 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

OPTIONS

White (AJE160-000-100) Orange (AJE160-000-800) Yellow (AJE160-000-200) Red (AJE160-000-600) Black (AJE160-001-100) Blue (AJE160-000-500) Green (AJE160-000-300) Grey (AJE160-000-400)

SAFETY STANDARDS

EN 397 • EN 50365



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS			
	Peak Mid		Impact Resistance 50 Joules
	Electrical Insulation 1000V		Molten Metal Yes
۲	Maximum Temperature +50°C		Minimum Temperature -40°C
HDPE	HDPE Shell Yes	ES .	Recyclable Shell
- <u> +</u> - - - -	Textile Harness	3D Ì	Depth Adjustment 3D Harness
	Slip Ratchet Slip		Universal Accessories Slot Yes
-	Ventilation No	°€€	Reflective Option Optional
	Integrated Eyewear Optional		ID card holder Optional
(bsi	BSI Kitemark Yes		Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional
	Optional 4 point chinstrap (EN397 Compliant) Optional	$\overline{\checkmark}$	JSPCheck Yes
$\overline{\langle}$	Product Weight		

FEATURES

372g



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® wheel ratchet or the OneTouch[™] slip ratchet.



CR2[™] Reflective

Using Class RA2, high intensity reflective. CR2[™] is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Supreme Comfort

A 6-point terylene cradle harness system & Egyptian cotton Chamlon[™] sweatband offers unrivalled comfort.



3D Adjustment

The comfortable textile harness features unique 1-2-3 point depth settings, offering the most precise fit attainable on an industrial safety helmet.

Accessories

A universal attachment slot enables firm fitting of a range of Surefit[™] safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.



RANGE

JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

LOGO

Front



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.







VIDEOS

- www.youtube.com/watch?v=PmDMMktdotQ
- www.youtube.com/watch?v=LdxMNctXLbg

DOWNLOADS

- Image Pack (ZIP)
- Declaration of Conformity (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.