

# TECHNICAL SPECIFICATION



## EYE AND FACE PROTECTION

### Stealth™ 9000

Smoke PremierShield™ K & N Rated / ASA770-15W-900



#### DESCRIPTION

The Stealth™ 9000 is a lightweight safety spectacle, weighing just 25g, with a wraparound 9 base curve polycarbonate lens. The slim stylish temples have been co-injection moulded with soft rubber to increase grip and provide excellent comfort. Stealth™ 9000 is available in a range of lens shades for various applications, with the option to add branding with logos and company colours.

#### OPTIONS

Amber PremierShield™ K & N Rated (ASA770-15P-900)  
Clear PremierShield™ K & N Rated (ASA770-15N-800)  
GW5 Hardia+™ Anti-Scratch Lens (ASA770-1CN-800)  
Indoor Outdoor Hardia™ HC lens. (ASA770-16R-100)  
Polarised Smoke Hardia+™ HC lens (ASA770-16X-600)  
Smoke + Blue Mirror Hardia™ HC lens (ASA770-16P-000)  
**Smoke PremierShield™ K & N Rated (ASA770-15W-900)**

#### SAFETY STANDARDS

EN 172 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 27 Jan 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.



## SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect  
Scale Number  
5



LIGHT TRANSMISSION BREAKDOWN Lens Shade number  
2.5



Manufacturer's Trademark  
JSP Dagger



Optical Class (1 – Class 1 – High quality for regular use. 2 –  
Class 2 – Medium quality for occasional use. 3 – Class 3 –  
Low quality for exceptional use)  
1



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °  
Maximum protection for glasses  
F



The letter T, immediately after the mechanical strength  
symbol, authorises use for high speed particles at extreme  
temperatures. (-5°C and +55°C) Optional  
T



Resistance to Surface Damage by Fine Particles (optional)  
K



Resistance to fogging (optional)  
N

## FEATURES



### Quality Lens

A lightweight safety spectacle, weighing just 25g.  
Features a wraparound 9.75 base curve Optical  
Class 1 polycarbonate lens precision cut for zero  
distortion.



### Comfort Temples

The slim stylish temples have been co-injection  
moulded with soft rubber to increase grip and  
provide excellent comfort levels.



### Comfort Nose Bridge

Built-in adjustable PVC nose piece for added  
comfort and stability. It rotates, as well as flexes,  
and adjusts to fit the shape of the nose.

## RANGE

**STEALTH  
9000**

## DOWNLOADS



[Image Pack \(ZIP\)](#)



[Declaration of Conformity \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jgpsafety.com](mailto:sales@jgpsafety.com) / Web: [www.jgpsafety.com](http://www.jgpsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jgpsafety.com](mailto:copyright@jgpsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 27 Jan 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.

