TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION

PressToCheck[™] P3 Dust Filters

Pack of 2 / BMN990-001-700





DESCRIPTION

PressToCheck[™] is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.97%, Low profile design maximising compatibility and low breathing resistance across the range.

F-4003 P3 dust encapsulated filters, featuring PressToCheck[™] technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

OPTIONS

Pack of 2 (BMN990-001-700)

SAFETY STANDARDS

EN 143



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS

No

Classification P3

Usage R (Reusable)



Activated Carbon Layer

Minimum Filtration Efficiency 99.97% To NIOSH Standard For P100 Filter

Maximum Total Inward Leakage (TIL) 0.05% when fitted to a Force10 Full Face Mask

Nominal Protection Factor 1000 When Fitted To A Force10 Full Face Mask

UK Assigned Protection Factor 40 When Fitted To A Force10 Full Face Mask

Latex free Yes

Filter Material Pleated Media

Filter Shelf Life 10 Years



Overall Product Weight 92g Per Pair

FEATURES



Increased Product Life

PressToCheck[™] encapsulated filters offer ultimate longevity – the durable design makes the filters easy to clean and reuse. Correct cleaning, maintenance and storage increases the useful life of the product.

VIDEOS

- youtu.be/1Y9G8E9kEXQ
- voutu.be/Ecyu_ftPPX4
- youtu.be/-oUSyP9_NsA

DOWNLOADS

- Image Pack (ZIP)
- Declaration of Conformity (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



 ∇

Filter Type P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging Yes – mandatory test in EN 143

Minimum Filtration Efficiency 99.95%

Maximum Total Inward Leakage (TIL) 2% when fitted to Force8 Half Mask

Nominal Protection Factor 48 When Fitted To A Force8 Half Mask

UK Assigned Protection Factor 20 When Fitted To A Force8 Half Mask



Type Press To Check Technology

Metal Free Yes

Filter Casing Material ABS



BSI Kitemark Yes